



Class Specification 26.00 cc Sprintcar

- 1/ Appearance - Must resemble a full size Sprintcar.
- 2/ Engine - Zenoah G2D70/ G230RC/ G260RC/ G270RC / SIKKTOY23
- Fitment of 25.4 kit allowed.
 - No other modifications allowed.
 - Tuned pipes can be used.
 - Carby can be rotated.
 - No reed valve engines allowed.
- 3/ Dimensions - wheelbase 24 inches (max)
- width 20 inches (max)
 - Length 39 Inches (max)
 - Chassis height Min 11 1/2 inches up to Max 15 3/4 inches
- 4/ Weight - no minimum for this class.
- 5/ Wings - Top 15 inches wide
- Side 18 inches long and 7 1/2 inches high.
 - Front 9 inches x 6 1/2 inches with 3 inch sides
- MUST NOT EXCEED**
- 6/ Wheels - Tyre width Open, rim width 4 1/2 inches
- 7/Suspension - No independent allowed.
- 8/ Frame - Tube or prefabricated.
- 9/ Driveline - Belt / Chain / Victa diff / Quick change must be locked
- No multi speed gearboxes allowed
- 10/ Brakes - All racecars must have an operational brake at all times
- 11/ Clutch - Mandatory.
- 12/ Fuel - Unleaded / premium unleaded with oil additive only.
- 13/ Kill Switch - Must be fitted and mounted on top RHR of roll cage